

RANGER® R6SS

Man-Portable Mid-Range Ground Surveillance Radar

APPLICATIONS

FORCE PROTECTION

BORDER SECURITY

VEHICLE DISMOUNT

ARTILLERY AND MORTAR

FIRE CORRECTION

UAS DETECTION



The man-portable Ranger® R6SS electronically-scanned, mid-range radars detect and track personnel and vehicles up to 15 kilometer ranges. Light and small, the Ranger R6SS provides best-in-class target detection and acquisition performance in a form factor that fits in a backpack or is easily mounted to a vehicle or permanent structure as part of an integrated solution. The low false alarm rate and extremely reliable operation builds operator trust and yields high operational availability.

The R6SS has a low minimum detection target velocity that allows detection of slow-moving threats such as walkers or crawlers. It uses a +/-45° scan sector to monitor a perimeter. Adding a pan and tilt provides a full 360° coverage every second. The R6SS provides fast and accurate detection of up to 512 threats simultaneously, allowing large areas to be continuously monitored in real time.

FEATURES

COMPLETE PERIMETER SECURITY

Extremely fast scanning at 4 times a second per panel, nothing is missed. The Ranger Panel Radars can scan a full 360° every second with a pan tilt mount, quickly detecting any ground threat from any direction.

HIGH-PERFORMANCE GROUND SURVEILLANCE

Built-in GPS and North finding capability, automatic target tracker and classification, and low false alarm rate deliver best-in-class performance.

BUILT FOR RUGGED ENVIRONMENTS

Panel Radars are MIL-STD-810G qualified and IP67 certified.

FAST, ACCURATE THREAT DETECTION

Panel Radars quickly detects up to 512 threats simultaneously while accurately displaying each target's location.

MAN-PORTABLE AND EASY TO INTEGRATE

R6SS can be transported in a backpack of a dismounted soldier and draws only 85W, giving it extreme deployment flexibility. With four mounting bolts and a single cable, the radar is easy to install in fixed installations.

SPECIFICATIONS

Parameters	R6SS
Instrumented range	15,000 m
Detection Range	
Person	6 km
Light Vehicle	10 km
Large Vehicle	15 km
MicroUAS	N/A
MiniUAS	N/A
Small UAS	N/A
Minimum Detection Range	10 m
Scan sector	± 45° (fixed) - 360° with P/T
Vertical coverage	≥ 4°
Number of simultaneously displayed tracks	Up to 512
Electronic scan rate	2 Hz or 4 Hz
Minimum Detection Velocity (MDV)	< 0.1 m/s
Accuracy	
Range Accuracy	± 3 m
Angular Accuracy (azimuth)	< 0.2 degree
Angular accuracy (elevation)	N/A
Power	
Power consumption	85 W nominal
Operating voltage	20 - 48 VDC
Overview	
Size (in)	14.7" x 14.4" x 4.3" (37 x 36 x 11 cm)
Weight	≤ 23.1 lbs (10.5 kg)
Operating frequency	X-Band
Connectivity	Ethernet
Environmental	MIL-STD-461F, IP67, MIL-STD-810G
Other Features	
Built-in GPS	Yes
Built-in compass	Yes



AMERICAS

27700 SW Parkway Ave
Wilsonville, OR 97070

EUROPE

2 Kings Hill Avenue - Kings Hill
West Malling, Kent ME19 4AQ
United Kingdom

Antennv. gen 6,
PO Box 737
SE-187 66 Täby
Sweden

MIDDLE EAST

Wadi Al Fey St.
Building 60, Office # 302
New Ministries Exit /
Khalifa Park Area
Abu Dhabi, U.A.E.

Office 127, First Floor
Akaria Plaza Building, Olaya Street
Riyadh, 11481, Saudi Arabia

ASIA

Meguro Tokyo Bldg. 5F,
2-13-17
Kami-Osaki, Shinagawa-ku.
Tokyo, 141-0021, Japan

Equipment described herein pertains to a Canadian origin product that is controlled as dual-use by the Canadian government. When in the United States or possessed by a US person, it may be subject to US Jurisdictions, which may require authorization to re-transfer to a foreign person. Imagery for illustration purposes only. Specifications are subject to change without notice. For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2021 Teledyne FLIR LLC. All rights reserved.

Revised on 08/31/21
Ranger R6SS_Datasheet-LTR 21-0831